

Puma EV

Technical specifications

Market: EDM LHD

Model year: 2026.75

Published: 1/29/2026



Technical specifications - Puma EV

Series	Gen-E	Gen-E Premium
Motor	ELECTRIC MOTOR #1 <BEV> - 46.8 kWh	ELECTRIC MOTOR #1 <BEV> - 46.8 kWh
Drive	FWD	FWD
Consumption & Emission		
Emission standard/Emission Code	Euro Zero Emission Vehicle / AX	Euro Zero Emission Vehicle / AX
Electric consumption combined [kWh/100 km]	13.03 - 14.62	13.68 - 14.62
Performance		
Power [kW(PS)]	123.5(168)	123.5(168)
Rated continuous power (30 min) [kW]	52	52
Transmission	Automatic Transmission	Automatic Transmission
Axle ratio	9.6	9.6
Maximum speed [km/h]	160	160
0-100 km/h [sec]	8	8
Torque [Nm]	290	290
Battery		
Usable battery capacity [kWh]	46.86	46.86
Range added in 10 mins [km]	121 - 135	121 - 135
Electric range combined [km]	386 - 417	386 - 404
Electric range city [km]	530 - 572	530 - 555
Peak charge power (DC) [kW]	100	100
Speed to charge (10-80%) (DC) [min]	26	26
Battery type	Lithium - ion(NMC)	Lithium - ion(NMC)
Weights		
Kerbweight [kg]	1563	1563
Gross vehicle mass [kg]	2015	2015
Gross train mass (12% gradient) [kg]	2765	2765
Payload [kg]	449	449
Roof load limit without panoramic roof (static) / with panoramic roof [kg]	75 / 0	75 / 0
Max. towable mass (braked) (12% gradient) [kg]	750	750
Max. towable mass (unbraked) [kg]	750	750
Vertical load limit [kg]	75	75

Other series based on the Gen-E Premium equipment variant - such as BlueCruise Edition - correspond to the basic model in their technical basic data.
The values stated refer to the standard equipment; these values may change due to the selection of optional extras and accessories.

Dimensions - Puma EV

Series	Gen-E	Gen-E Premium
Motor	ELECTRIC MOTOR #1 <BEV> - 46.8 kWh	ELECTRIC MOTOR #1 <BEV> - 46.8 kWh
Drive	FWD	FWD
External Dimensions		
Overall length without tow bar / with tow bar [mm]	4214 / 4313	4214 / 4313
Overall height (unloaded) [mm]	1555	1555
Overall width without mirrors / with folded-back mirrors / with mirrors [mm]	- / 1805 / 1930	- / 1805 / 1930
Front overhang / Rear overhang [mm] incl. licence plate	863 / 763	863 / 763
Wheelbase [mm]	2588	2588
Front track / Rear track [mm]	1567 / 1540	1567 / 1540
Internal Passenger Dimensions		
Seating capacity [seats]	5	5
1st seat row headroom without panoramic roof / with panoramic roof [mm]	1000 / 983	1000 / 983
1st seat row shoulder room [mm]	1348	1348
1st seat row hip room [mm]	1311	1311
1st seat row legroom (max. with seat in rearmost midheight position) [mm]	1127	1127
2nd seat row headroom without panoramic roof / with panoramic roof [mm]	965 / 957	965 / 957
2nd seat row shoulder room [mm]	1320	1320
2nd seat row hip room [mm]	1278	1278
2nd seat row legroom (max. with seat in rearmost midheight position) [mm]	786	786
Cargo & Loading Dimensions		
Loaded volume to package tray [l] (without load floor) (HEV)	523	523
Loaded volume to roof 5-seat [l] (without load floor) (HEV)	574	574
Loaded volume to roof 2-seat [l] (without load floor) (HEV)	1283	1283
Front trunk volume [l]	43	43
Load opening height (max.) [mm]	603	603
Load opening width [mm]	982	982
Loading height (max.) [mm]	865	865
Loading width between wheel houses [mm]	1000	1000
Loading length at floor to 2nd seat row [mm]	725	725
Loading length at floor to 1st seat row (2nd row seats folded) [mm]	1479	1479
Lift in height [mm]	771	771
Practical Clearance & Maneuverability		
Ground clearance (unloaded / fully loaded) [mm]	157 / 129	157 / 129
Turning circle, kerb to kerb [m]	10.5	10.5

Other series based on the Gen-E Premium equipment variant - such as BlueCruise Edition - correspond to the basic model in their technical basic data.
The values stated refer to the standard equipment; these values may change due to the selection of optional extras and accessories.